



台下式洗杯/碗機VMU-7K UNDER-COUNTER GLASS AND DISH WASHER

特點與優勢:

- 可視化電子面板，實時顯示機器工作狀態;
- 高亮LED溫度顯示板，一目了然;
- 雙層門結構設計，節能降噪，改善操作環境;
- 緊湊型結構設計，節省空間;
- 高效的溫控及噴淋溫度限制程序設計，獲得最佳噴淋效果;
- 內凹防堵噴嘴設計，擴大扇形水幕面積，清潔更徹底。



CHARACTERISTICS AND ADVANTAGES

- Visual electronic operation panel displays the working status of machine in real time.
- Highlighted LED temperature display makes it clear at a glance.
- Double-skin door,energy saving and noise reduction,improves the work environment.
- Compact structure design saves space.
- Effective temperature control and rinse temperature limit program design achieve the best rinse effect.
- Inward curving nozzles, broadening the fan-shape water curtain, make the cleaning thoroughly .

可選配置 Optional Configuration

名稱/型號	NAME/MODEL	VMU-7K	
電源要求	Power requirements	380V/50Hz/3Ph	220V/50Hz/1Ph
進水溫度(攝氏度)	Incoming water temperature(°C)	10~60	40~60
水槽加熱功率(千瓦)	Tank heater(Kw)	2	2
漂洗加熱功率(千瓦)	Booster heater(Kw)	6	2
清洗泵功率(千瓦)	Wash pump(Kw)	0.4	0.4
總功率(千瓦)	Total power(Kw)	6.4	2.4
總電流(安)	Total current(A)	11	11
電源線截面(平方毫米)	Cross section of cable(mm ²)	4	4
空氣開關額定功率(安)	Rate current of air circuit breaker(A)	25	25







安裝接駁要求 Requirements On Installation Connection

- 電力安裝需要220V/50Hz/單相三線或380V/50Hz/三相五線，外部需加裝獨立的空氣開關；
- 機器可直接與一般供水系統連接，最低水壓必須達到2Kg/cm²。
- Power Requirements: 220V/50Hz/1Ph+Neutral + Ground or 380V/50Hz/3Ph+Neutral + Ground with a separate external air circuit breaker.
- The machine can be directly connected to water supply system, the lowest incoming water pressure should be 2Kg/cm².

技術參數 Parameters

名稱/型號	NAME/MODEL	VMU-7K
加熱方式	Heating	電加熱/Electricity
外形尺寸(毫米)	External dimension (mm)	576x600x796
最大洗滌高度(毫米)	Max entry height (mm)	316
機器入口寬度(毫米)	Passing width (mm)	508
最大洗滌量(筐/小時)	Max capacity (rack/hour)	40
耗水量(升/筐)	Water consumption (liter/rack)	2.6
水箱容積(升)	Wash tank capacity (liter)	23
升溫器容積(升)	Booster capacity (liter)	5.5
洗滌溫度(℃)	Wash temperature (°C)	55~60
漂洗溫度(℃)	Rinse temperature (°C)	82~90
洗滌周期(秒)	Wash cycle (s)	90/120
進水管徑(英寸)	Diameter of the water inlet hose (in)	3/4
排水管徑(毫米)	Diameter of drain pipe (mm)	31
進水壓力(千克/平方厘米)	Incoming water pressure (Kg/cm ²)	2~5
進水硬度(克/升)	Incoming water hardness (g/l)	0.034~0.103



1. 進水口 Water Inlet
2. 排水口 Drain Outlet
3. 電源線接口 Cable Connection

適用的場所Applicable Places: 小型餐廳、咖啡廳、酒吧等場所
Small restaurants, coffee shops, bars and other catering industries